

COOLING TOWERS



About EVAPCO



EVAPCO for LIFE

EVAPCO is more than a name. We are the global innovator in heat transfer solutions for the commercial HVAC, industrial refrigeration, power, and industrial process markets. We pledge to make everyday life easier, more comfortable, more reliable, and more sustainable for people everywhere.

OUR COMMITMENT


We never stop innovating. We set out to find groundbreaking solutions that transform the way the world works for the better. It's why we have more than 50 active U.S. Patents and nearly 200 foreign counterparts. We also guarantee performance by putting every solution through rigorous research and testing to ensure maximum efficiency and reliability.



PROTECTING THE ENVIRONMENT

Innovation and environmental sustainability go hand-in-hand at EVAPCO. Our industrial heat transfer equipment not only conserves natural resources and helps reduce noise pollution, but also features recycled steel content in construction. Our stainless steel units are constructed of panels that contain up to 75% of recycled content and our galvanized units contain over 80%. From sound reduction to water conservation to chemical elimination, we are developing new technologies that deliver ultimate operating advantages to our clients while protecting the planet for every generation to come.





THROUGH THE YEARS

Since the beginning,
we have never stopped
INNOVATING.

EVAPCO's cooling tower solutions are highly engineered with quality components and manufactured to exacting standards. The durable materials of construction ensure the longevity expected of EVAPCO products. EVAPCO offers an extensive selection of cooling towers for new construction and replacement projects. Our cooling tower products are:



CTI certified, IBC compliant and ASHRAE 90.1 compliant


With customer satisfaction as our number one priority, we strive to provide you with the best solution for every project.



DATA
CENTERS



INDUSTRIAL
PROCESS



COMFORT
COOLING

* Mark owned by the Cooling Technology Institute
† Mark owned by ASHRAE

KNOW YOUR OPTIONS

As the leader in evaporative technology, EVAPCO offers a number of open cooling tower solutions, including induced draft, forced draft, counterflow, and crossflow options. Allow us to optimize our state-of-the-art equipment to meet the needs of your application, all while maintaining the latest industry standards.



AT ATLAS

The AT Atlas is a modular, induced draft, counterflow cooling tower. It is specifically designed to match the capacity and efficiency of a field-erected cooling tower with a factory-assembled approach. The Atlas features the same high efficiency EVAPAK® fill as the reliable AT, as well as our pressurized, corrosion-free PVC water distribution system and maintenance-free EvapJet™ nozzles. All Atlas units come standard with our Water and Sight Tight (WST) air inlet louvers, plus an industrial gear drive with external motor mount.

*When compared to other factory-assembled single cell towers.

Experience a cooling capacity increase of up to 60% per cell and fan power reduction up to 40%.*

Shorten lead time by up to 60%†

Benefit large tonnage applications > 4,000 tons

Maximize available space by arriving in pre-assembled modules to reduce the need for assembly area onsite

Reduce installation costs†

† When compared to field-erected cooling towers

KNOW YOUR

AT

The AT is an induced draft, counterflow cooling tower, designed to take full advantage of the space around the tower by drawing in air on all sides. EVAPCO's high efficiency, bottom-supported EVAPAK® fill maximizes cooling capacity while doubling as an internal working platform. The clog-resistant EvapJet™ nozzles, the hardware-free Water and Sight Tight (WST) air inlet louvers, pressurized and non-corrosive PVC water distribution system, extended bearing lubrication lines, and many other innovative features simplify routine maintenance on the AT unit.



Reduce operating weight and lifting weight

the stepped basin design provides lower operating weight; reducing weight of heaviest section with option to lift in 3 pieces

Accommodate compact plan area(s)
air intake on all 4 sides allows ATs to be used in tight layouts

Reduce power consumption with high efficiency operation

Offer flexibility in connection and accessory locations

Boost freeze protection
encasing fill completely in steel lowers chance of ice formation; optional drip angles, internal wind baffle, and basin heaters can further decrease freeze potential

The AXS is an induced draft, crossflow cooling tower, ideal for easy system expansion and high tonnage applications. EVAPCO's modular hot water basins allow for simple change-out and the open plenum section allows for easy access to the drive system and basin through the large access doors. The AXS's innovative bottom-supported fill design allows for easier maintenance of the cold water basin.



AXS

Maximize plan area

multi-cell AXS selections can be stacked side-by-side with little to no impact on capacity

Reduce power consumption with high efficiency operation

Secure large tonnage applications with limited footprint

Facilitate interior maintenance with large plenum

Replace existing crossflow installations

FEATURES AND APPLICATIONS

EVAPCO has dramatically changed the water treatment game with the introduction of Smart Shield®. Available as a complete water treatment system for open evaporative cooling applications. Water treatment has never been easier or more dependable.



- Accommodate height restricted applications**
- Satisfy sound requirements**
multiple sound attenuation options are available
- Adapt to ducted and/or high external static pressure applications**
- Provide freeze protection**
with fill completely encased in steel, there's a lower chance of ice formation

TARGET APPLICATIONS/ADVANTAGES



- Adapt to ducted and/or high external static pressure applications**
- Satisfy sound requirements**
multiple sound attenuation options are available
- Provide freeze protection**
with fill completely encased in steel, there's a lower chance of ice formation
- Accommodate indoor applications with space restrictions**


LPT

The LPT is a forced draft, counterflow cooling tower, designed for indoor and ducted applications. Positioning the centrifugal fan on the end of the basin and casing sections allows for the lowest profile design of all our open towers, making the LPT ideal for height restricted applications. The LPT features a first stage sound attenuating casing around the fan section.

LSTE

The LSTE is a forced draft, counterflow cooling tower, especially suited for indoor and ducted layouts due to its use of centrifugal fans. With inherently lower sound levels and its integrated fan and basin section, the LSTE is ideal for replacements and tight layouts.


Have questions? Read on to learn more about each of these innovative options or visit evapcoasia.com to find your local EVAPCO representative now.



THE AT ATLAS SERIES

Principle of Operation

This cutaway graphic of the AT Atlas illustrates the basic functionality of our modular, induced draft, counterflow cooling tower. Hot water from the heat source is pumped to the water distribution system at the top of the tower. The water is distributed over the wet deck fill by means of our EvapJet™ nozzles. Simultaneously, air is drawn in through the air inlet louvers at the base of the tower on all four sides and travels upward through the wet deck fill **opposite** the water flow. The cooled water drains to the basin at the bottom of the tower and is returned to the heat source.



High-Efficiency Drift Eliminators

- Limit the drift rate down to 0.0005% of the recirculating water rate
- Assembled in easily removable sections
- Constructed of inert PVC, effectively eliminating corrosion

EVAPAK® Fill

- Specially designed to induce a highly turbulent mix of air and water for superior heat transfer
- Special drainage tips allow high water loadings without excessive pressure drops
- Bottom-supported cross-fluted sheets are bonded together to enhance its structural integrity
- Usable as a working platform for internal access to the fan and drive system




Water and Sight Tight (WST) Air Inlet Louvers

- Framed in same material as tower basin
- Improved design to keep sunlight out—preventing algae growth
- Keeps water in while keeping dirt and debris out
- Hardware free, easily removable
- 360 degree access to basin



Clean Pan Sloped Basin Design

- Designed to completely drain the cold water basin
- Helps prevent buildup of sediment and biological film
- Eliminates standing water after drain down





Mechanical Equipment

- Only select suppliers specializing in cooling tower products chosen to provide associated fans, gearboxes, drive shafts, etc.
- Must meet strict quality control requirements
- Produces airflow necessary for peak thermal performance



Robust Design and Materials

Built with industrial-grade materials and engineered to withstand the demands of HVAC and industrial applications

- Heavy-gauge steel structure, galvanized or stainless steel
- Energy-efficient PVC heat exchange fill media
- Standard motor outside airstream

Pressurized Water Distribution System

- EvapJet™ nozzles provide thermal performance gain
- Non-corrosive PVC construction
- Large orifice nozzles prevent clogging and are threaded for easy removal and positive positioning
- Each nozzle provides a large uniform spray pattern



Access

- Removable louvers offer 360 degree basin access for easy inspection and maintenance

Louver Access Door

- Hinged access panel with quick-release mechanism
- Allows easy access to perform routine maintenance and inspection of the makeup assembly, strainer screen, and basin




*
Certified Thermal Performance

*Mark owned by the Cooling Technology Institute

THE AT SERIES

Principle of Operation

Like the Atlas, the AT shares the functionality of an induced draft, counterflow cooling tower. Hot water from the heat source is pumped to the water distribution system at the top of the tower. The water is distributed over the wet deck fill by means of our EvapJet™ nozzles. Simultaneously, air is drawn in through the air inlet louvers at the base of the tower on all four sides and travels upward through the wet deck fill **opposite** the water flow. The cooled water drains to the basin at the bottom of the tower and is returned to the heat source.



EVAPCO Power-Band Drive System

- Easy maintenance, heavy-duty drive system
- Standard heavy-duty pillow-block bearings with a minimum L_{10} life of 100,000 hours
- Extended lube lines
- External motor/belt adjustment
- Solid-back multi-groove belts and totally enclosed motors are standard
- Belts constructed of neoprene and polyester cords, sized for 150% of the motor nameplate horsepower to ensure long, trouble-free operation
- Gear drive optional



Water and Sight Tight (WST) Air Inlet Louvers

- Easily removable for access
- Framed in same material as tower basin
- Designed to keep sunlight out—preventing algae growth
- Keeps water in while keeping dirt and debris out



Clean Pan Sloped Basin Design

- Designed to completely drain the cold water basin
- Helps prevent buildup of sediment and biological film
- Eliminates standing water after drain down

IBC* Compliant & OSHPD† Designs

- All standard models meet IBC requirements
- Upgraded designs for high seismic and wind load areas
- Upgraded designs can also be used for projects requiring OSHPD approval



*International Building Code

†Office of Statewide Health Planning and Development



Optional Motor Davit & Working Platform

- Motor davit and bracket option for easy motor and fan removal
- Also available for gearbox removal
- Custom platform and ladder arrangements available
- Provides a robust self-supporting working surface for the service mechanic
- Motors positioned to be easily accessible and serviceable


Water Distribution System

- EvapJet™ nozzles provide thermal performance gain
- Non-corrosive PVC construction
- Large orifice nozzles prevent clogging and are threaded for easy removal and positive positioning
- Each nozzle provides a large uniform spray pattern



EVAPAK® Fill

- Specially designed to induce a highly turbulent mix of air and water for superior heat transfer
- Special drainage tips allow high water loadings without excessive pressure drops
- Bottom-supported cross-fluted sheets are bonded together to enhance its structural integrity
- Usable as a working platform for internal access to the fan and drive system



Louver Access Door

- Hinged access panel with quick-release mechanism
- Allows easy access to perform routine maintenance and inspection of the makeup assembly, strainer screen, and basin
- Standard on models with louvers 1.5m and taller




Certified Thermal Performance

***Mark owned by the Cooling Technology Institute*

THE AXS SERIES


Principle of Operation

The induced draft, crossflow AXS collects warm water from the heat source in the water distribution system at the top of the tower. The water is distributed over the wet deck fill through large orifice nozzles. Simultaneously, air is drawn in through the air inlet louvers at the ends of the tower and travels **horizontally** through the wet deck fill across the water flow. The cooled water drains to the basin at the bottom of the tower and is returned to the heat source.



Modular Hot Water Basins

- Steel covers in easy to handle sections
- Large orifice, non-clog nozzles
- Integral weir dams to accommodate at least 50% design flow



XPak™ Crossflow Fill

- High efficiency bonded block fill
- Polyvinyl Chloride (PVC)
- Impervious to rot, decay and biological attack
- Integral louvers and drift eliminators
- Easy to handle
- Flame spread rating of <25 per ASTM E84



Certified Thermal Performance

*Mark owned by the Cooling Technology Institute

Cold Water Basin End Covers

- Prevents sunlight and debris from entering basin
- Easy lift-off with handles



EVAPCO Power-Band Drive System

- Easy maintenance, heavy-duty drive system
- Standard heavy-duty pillow-block bearings with a minimum L_{10} life of 100,000 hours
- Extended lube lines
- Solid-back multi-groove belts and totally enclosed motors are standard
- Belts constructed of neoprene and polyester cords, sized for 150% of the motor nameplate horsepower to ensure long, trouble-free operation
- Gear drive optional

Single Side Inlet


- Self-balancing
- Includes all interior piping (factory installed)
- Includes all exterior piping (ships loose for field installation)

Two (2) Oversized Access Doors

- Swing-in doors on each side wall
- Easy access to interior of unit

Bottom-Supported Fill


- Non-sagging
- Minimum 75mm above basin floor
- Easy to clean under
- Allows room for optional sump sweeper piping



THE LSTE SERIES

Principle of Operation

The forced draft, counterflow LSTE distributes water over the wet deck fill while simultaneously forcing air through the air inlet at the base of the tower. This tower is especially suited to indoor or ducted layouts due to its ability to handle external static pressure. This classic design is also ideal for exact replacement projects.



EVAPAK® Fill

- Specially designed to induce a highly turbulent mix of air and water for superior heat transfer
- Special drainage tips allow high water loadings without excessive pressure drops
- Bottom-supported cross-fluted sheets are bonded together to enhance its structural integrity

Easy Field Assembly

- Ensures easy assembly and fewer fasteners
- Incorporates self-guiding channels to guide the casing section into position improving the quality of the field seam




Certified Thermal Performance

**Mark owned by the Cooling Technology Institute*



Clean Pan Design

- Sloped design allows water to drain completely from cold water basin
- Easier removal of dirt and debris




Totally Enclosed Fan Motors & Superior Drive System

- Located in dry, incoming air-stream, allowing normal maintenance to be done from the outside of the unit
- Double sealed bearings
- Double dipped & baked treatment of windings with a polyester varnish
- Standard with space heaters to eliminate condensation while idle



THE LPT SERIES




Principle of Operation

The forced draft, counterflow LPT follows the same principle of operation as the LSTE, but with slight reconfiguration to better suit low profile applications.


PVC Spray Distribution Header

- Nozzles are threaded into the header to ensure proper orientation
- Fixed position nozzles require little maintenance
- Large orifice nozzle with integral sludge ring to prevent clogging
- Threaded end-caps on distribution piping for ease of cleaning



High Efficiency Drift Eliminators

- Advanced design limits maximum drift rate to 0.001% of the recirculated water rate
- Corrosion resistant PVC for long life



Double-Brake Flange Joints

- Stronger than single-brake designs by others
- Ships in single piece
- Greater structural integrity

Fan Housing

- Standard on all LPT series selections
- Drive system is completely enclosed in a protective housing
- First stage sound attenuation, providing sound reduction



Easy to Service Motor & Drive System

- Belt tensioning and bearing lubrication can be performed from outside the unit
- Locking mechanism can also be used as a wrench to adjust the belt tension
- Motor is fully accessible by removing one inlet screen
- Split fan housings allow removal of all mechanical equipment through the end of the unit



Certified Thermal Performance

*Mark owned by the Cooling Technology Institute


HEAT TRANSFER MEDIA

With EVAPCO, you get a partner you can count on to keep you at the cutting edge of your field. That's because we build innovation into every HVAC solution that we deliver to you.

EVAPAK® Counterflow Fill

Used inside all EVAPCO counterflow induced draft and forced draft cooling towers. Our EVAPAK® counterflow fill is specially designed to induce a highly turbulent mix of air and water for superior heat transfer. Special drainage tips allow high water loadings without excessive pressure drops.

EVAPAK® counterflow fill is constructed of inert polyvinyl chloride (PVC), so it will not rot or decay. It can also withstand water temperatures of 130° F /55° C. An option for higher water temperatures is also available. Consult your EVAPCO sales representative to learn more.



The bottom support of the fill section, combined with the unique way in which EVAPAK® counterflow fill's cross-fluted sheets are bonded together, greatly enhances the fill's structural integrity, making it usable as a working platform.

EVAPAK® is also self-extinguishing with a flame spread rating of <25 per ASTM-E84.

Optional Fill Types

EVAPCO also offers alternate fills as an option on most cooling towers for special applications. Consult your local EVAPCO sales representative for further details.


Titan-Pak fill media comes in a cross-fluted design and is constructed entirely of stainless steel, making it noncombustible.

Wide-Pak cross-fluted fill is often used in dirty water applications. It has a lower surface area than EVAPAK® fill; therefore, towers need to be sized appropriately to account for the change in available capacity.

VERTICLEAN® vertical-fluted fill is often used in dirty water applications and can handle oil or greases in the system up to 5 ppm. VERTICLEAN® fill has a lower surface area than the Wide-Pak fill; therefore, towers need to be sized appropriately to account for the change in available capacity.

XPak™ Crossflow Fill

The AXS features bonded block fill with both integral louvers and drift eliminators. The XPak™ Crossflow fill is bottom supported, preventing any sagging and allowing for easier routine basin maintenance. Flame spread rating of <25 per ASTM-E84.



MATERIALS OF CONSTRUCTION

EVAPCO is committed to using only the highest quality, industrial grade materials in all our cooling towers ensuring absolute reliability and longevity.

Polyvinyl Chloride (PVC)

Schedule 40 piping is utilized for our pressurized water distribution for superior corrosion resistance and to minimize water distribution maintenance required. Fill media is constructed of PVC with a cross-fluted design and is resistant to rot, decay and biological attack.

G-235 Galvanized Steel

Our cooling towers utilize heavy gauge mill hot-dip galvanized steel. All galvanized steel is coated with a minimum of 2.35 ounces of zinc per square foot of area (G-235 Hot-Dip Galvanized Steel designation). During fabrication, all exposed galvanized steel panel edges are coated with 95% pure zinc-rich compound.



304/304L Stainless Steel

Our cooling towers may be upgraded to 304/304L stainless steel. High levels of chromium and nickel allow stainless steel to form a renewable chromium-oxide layer. This ultra-thin layer protects wetted areas, such as the cold and hot water basins from general corrosion. The higher chromium and nickel content greatly impact corrosion resistance properties.

316/316L Stainless Steel

316/316L stainless steel is the superior material choice for the cooling tower market. It is comprised of 2-3% molybdenum, which gives the surface film a high degree of protection against chloride attack. For coastal regions, high temperature applications, and/or areas with high chloride concentration in the makeup water, this advantage is ideal. Using this material can increase the longevity of your cooling tower and help protect the towers' integrity in harsh environments.

The table below summarizes the metallurgy of common stainless-steel options.

Type	Chromium Content wt%	Nickel Content wt%	Molybdenum Content wt%	Carbon Content wt%
301L*	16.0 - 18.0	6.0 - 8.0	0.00	0.03
304	18.0 - 20.0	8.0 - 12.0	0.00	0.08
304L	18.0 - 20.0	8.0 - 12.0	0.00	0.03
316	16.0 - 18.0	10.0 - 14.0	2.0 - 3.0	0.08
316L	16.0 - 18.0	10.0 - 14.0	2.0 - 3.0	0.03

*301L is not suitable for use in cooling towers

DRIVE SYSTEMS

Power-Band Drive System Design

EVAPCO Cooling Towers feature the highly efficient Power-Band drive system. The Power-Band drive system consistently performs with trouble-free operation in the most severe conditions.

Power-Band Belt

The Power-Band belt is a solid-backed multi-groove belt designed for cooling tower service. The drive belt is sized for 150 percent of the motor nameplate horsepower and constructed of neoprene with polyester chords. Band belts are field-proven with over 30 years of operation.

Drive System Sheaves

Drive system sheaves are constructed of an aluminum alloy for corrosion resistance in the humid cooling tower environment.

Fan Shaft Bearings

For ultimate reliability, EVAPCO cooling towers come equipped with heavy-duty, pillow block bearings. These fan shaft bearings feature extended lubrication lines to grease fittings located on the exterior of the unit for easy maintenance. Additionally, they offer a minimum 100,000 hrs. L_{10} life.


Fan Motors

All EVAPCO cooling towers utilize fan motors designed specifically for evaporative cooling applications, with space heaters as standard. **Fan motors, which are compatible with variable frequency drive (VFD) systems, come standard on all cooling tower models. Alternative fan motor options are available as follows:**

- Premium efficient
- Two speed single winding
- Two speed two winding
- Explosion proof

Gear Drive Systems (Optional)


Design features and ratings are in accordance with, or exceed, the minimum requirements of AGMA (American Gear Manufacturers Association) and CTI standards. Castings are rigidly designed and constructed to absorb internal and external loads. Our gear drive system has an industry leading L_{10} bearing life exceeding 100,000 hours. Both the couplings and the gear drive are selected with a 2.0 service factor per AGMA and CTI recommendations.



Power-Band Belt



TEAO Fan Motor



Gear Drive System (Shown with Optional Super Low Sound Fan)

LOW SOUND SOLUTIONS

Super Low Sound Fan (Optional)

When you're tasked with achieving the lowest sound levels possible, there's only one choice: the EVAPCO Super Low Sound Fan. It's the quietest, most noise-efficient fan in the industry. Made of heavy-duty reinforced polyester, the ultra-wide chord blades have a forward swept design and rounded edges to minimize the sound caused by flow separation and vortex shedding. The end result is a sound pressure level 9 to 15 dB(A) lower than standard fans, depending on the specific unit selection and measurement location, with **no impact on thermal capacity**.



Water Silencer – Reduces Water Noise up to 7 dB(A) (Optional)


Located in the cold water basin, EVAPCO's water silencer reduces the high frequency noise associated with falling water and is capable of lowering overall sound levels 4 to 7 dB(A) when measured at 1.5m from the side or end of the unit. When water is circulated with fans off, the results are even greater: as much as 9 to 12 dB(A) lower at the same measured distance (depending on water loading and louver height). Constructed of lightweight PVC sections, the silencer can be easily removed for access to the basin area. It will have no impact on thermal performance and is CTI certified.

Note: Not available on 1.2m wide models.



Forced-Draft Sound Attenuation (Optional)

EVAPCO's forced-draft towers feature a centrifugal fan design that operates at lower sound levels, making the units ideal for installations where noise is a concern. The unit's design can be customized with a variety of intake stages and discharge attenuation packages to greatly reduce sound levels even further for extremely noise sensitive applications.



Offset Sound Attenuation Walls (Optional)

Add EVAPCO's CTI-certified offset sound attenuation walls to your super low sound fan and water silencer options for the ultimate sound control. Constructed of G-235 galvanized steel and lined inside with acoustical padding, the walls will typically reduce the 15m free-field sound level by an additional 3 dB(A). Stainless steel construction also available. Requires external support by others.

AT Fan Discharge Attenuation (Optional)

Up to 10 dB(A) Reduction


This options allows for further sound reduction of the unit. The attenuator can be used with the standard AT fan or in combination with the Low Sound or Super Low Sound Fan option. The discharge attenuator is a factory-assembled straight-sided discharge hood designed to reduce overall discharge sound levels at full fan speed by 5 dB(A) to 10 dB(A), depending on specific unit selection and measurement location with a minimal impact to thermal performance. It is constructed of G-235 galvanized steel as standard (options available for stainless steel) and includes insulated walls and a low pressure drop baffling system that is acoustically lined with high density fiberglass. The discharge attenuator is self-supported by the unit and is shipped loose for field mounting. A heavy gauge, hot-dip galvanized steel fan guard covers the discharge attenuator to prevent debris from entering the attenuator.

WATER TREATMENT SOLUTIONS



Smart Shield® Solid Chemical Water Treatment System

EVAPCO's product innovation continues with the introduction of Smart Shield® factory assembled solid chemistry water treatment for open cooling systems. Smart Shield® is available in two unique skid-mounted systems: **Controlled Release** and **Monitored Release**, to protect a broad range of evaporative cooling water applications. In addition, these new Smart Shield® systems incorporate a modular design to simplify installation and minimize the floor space required in the mechanical room for the water treatment of your evaporative cooling equipment.



The skid-mounted Smart Shield® feeders are designed to control the release of granular and solid water treatment chemicals. Taking the water out of liquid water treatment chemicals provides an easier and more sustainable treatment approach that reduces shipping, handling, and storage weights by up to 80%.

Contact your local EVAPCO representative to learn whether the Controlled Release or Monitored Release System is right for your open evaporative cooling application.

Learn more about Smart Shield® at evapcoasia.com.

EVAPCO's Water Systems division focuses on the application and on-going development of chemical, hybrid, and non-chemical water treatment systems. This division utilizes advanced technologies and equipment in the field of analytical chemistry, including Ion Chromatography and Atomic Absorption Spectroscopy, giving EVAPCO the ability to conduct fast and accurate analyses of these water treatment systems.



Note:



WORLDWIDE MANUFACTURING FACILITIES



★ World Headquarters/
Research and
Development Center

■ EVAPCO Facilities



EVAPCO, Inc. — World Headquarters & Research / Development Center

P.O. Box 1300 • Westminster, MD 21158 USA
410.756.2600 • marketing@evapco.com • evapco.com

North America

EVAPCO, Inc. World Headquarters

Westminster, MD USA
410.756.2600
marketing@evapco.com

EVAPCO East

Taneytown, MD USA
410.756.2600
marketing@evapco.com

EVAPCO East

Key Building
Taneytown, MD USA
410.756.2600
marketing@evapco.com

EVAPCO Midwest

Greenup, IL USA
217.923.3431
evapcomw@evapcomw.com

EVAPCO West

Madera, CA USA
559.673.2207
contact@evapcowest.com

EVAPCO Iowa

Lake View, IA USA
712.657.3223

EVAPCO Iowa

Sales & Engineering
Medford, MN USA
507.446.8005
evapcomn@evapcomn.com

EVAPCO Newton

Newton, IL USA
618.783.3433
evapcomw@evapcomw.com

Evapcold Manufacturing

Greenup, IL USA
217.923.3431
evapcomw@evapcomw.com

EVAPCO Dry Cooling, Inc.

Littleton, CO USA
908.895.3236
info@evapcodc.com
Spare Parts: 908.895.3236
Spare Parts: spares@evapcodc.com

EVAPCO Dry Cooling, Inc.

Bridgewater, NJ USA
908.379.2665
info@evapcodc.com

EVAPCO Power México S. de R.L. de C.V.

Mexico City, Mexico
(52) 55.8421.9260
info@evapcodc.com

Refrigeration Vessels & Systems Corporation

A wholly owned subsidiary of EVAPCO, Inc.
Bryan, TX USA
979.778.0095
rsvs@rsvscorp.com

EvapTech, Inc.

A wholly owned subsidiary of EVAPCO, Inc.
Edwardsville, KS USA
913.322.5165
marketing@evaptech.com

Tower Components, Inc.

A wholly owned subsidiary of EVAPCO, Inc.
Ramseur, NC USA
336.824.2102
mail@towercomponentsinc.com

EVAPCO Alcoil, Inc.

A wholly owned subsidiary of EVAPCO, Inc.
York, PA USA
717.347.7500
info@evapco-alcoil.com

Europe

EVAPCO Europe BVBA European Headquarters

Tongerren, Belgium
(32) 12.39.50.29
evapco.europe@evapco.be

EVAPCO Europe, S.r.l.

Milan, Italy
(39) 02.939.9041
evapcoeuropa@evapco.it

EVAPCO Europe, S.r.l.

Sondrio, Italy

EVAPCO Europe GmbH

Meerbusch, Germany
(49) 2159.69560
info@evapco.de

EVAPCO Air Solutions

A wholly owned subsidiary of EVAPCO, Inc.
Aabybro, Denmark
(45) 9824.4999
info@evapco.dk

EVAPCO Air Solutions GmbH

Garbsen, Germany
(49) 5137.938750
info@evapcoas.de

Evap Egypt Engineering Industries Co.

A licensed manufacturer of EVAPCO, Inc.
Nasr City, Cairo, Egypt
(202) 24044997 / (202) 24044998
mmanz@tiba-group.com /
hany@tiba-group.com

EVAPCO Middle East DMCC

Dubai, United Arab Emirates
(971) 4.448.7242
info@evapco.ae

EVAPCO S.A. (Pty.) Ltd.

A licensed manufacturer of EVAPCO, Inc.
Isando, South Africa
(27) 11.392.6630
evapco@evapco.co.za

Asia Pacific

EVAPCO Asia Pacific Headquarters

Baoshan Industrial Zone
Shanghai, P.R. China
(86) 21.6687.7786
marketing@evapcochina.com

EVAPCO (Shanghai) Refrigeration Equipment Co., Ltd.

Baoshan Industrial Zone, Shanghai, P.R. China
(86) 21.6687.7786
marketing@evapcochina.com

EVAPCO (Beijing) Refrigeration Equipment Co., Ltd.

Huairou District, Beijing, P.R. China
(86) 10.6166.7238
marketing@evapcochina.com

EVAPCO Air Cooling Systems (Jiaxing) Company, Ltd.

Jiaxing, Zhejiang, P.R. China
(86) 573.8311.9379
info@evapcochina.com

EVAPCO Australia (Pty.) Ltd.

Riverstone, NSW, Australia
(61) 02.9627.3322
sales@evapco.com.au

EvapTech Asia Pacific Sdn. Bhd

A wholly owned subsidiary of EvapTech, Inc.
Puchong, Selangor, Malaysia
(60) 3.8070.7255
marketing-ap@evaptech.com

South America

EVAPCO Brasil

Equipamentos Industriais Ltda.
Indaiatuba, São Paulo, Brazil
(55) 11.5681.2000
vendas@evapco.com.br

FanTR Technology Resources

Indaiatuba, São Paulo, Brazil
(55) 11.4025.1670
fantr@fantr.com

Bulletin CT21MRKT
3M/10-21/YGS

©2021 EVAPCO, Inc.

Committed to making life easier, more reliable and more sustainable for people everywhere