OTES: IMP FAN MOTOR LOCATION IMP FAN MOTOR LOCATION IMP STATE OF THE SECTION IS UPPER SECTION MAP DENDITS MALE PIPE THREAD FOR DENOTES FEMALE PIPE THREAD FOR DENOTES FEMALE PIPE THREAD FOR DENOTES FEMALE PIPE THREAD BEY DENOTES BEVELED FOR WELDING GVD DENOTES GROVED FLORE OF SEVELED FOR MALE PIPE THREAD FACE D FACE	CLOSED CIRCUIT COOLER	EVADCO TRIC EVCIDEO WB3TM1806-DRC-SF	REV.
DEPOTES SEMALE PIPE THREAD BEYD DENOTES SEMALE PIPE THREAD BEYD DENOTES SEMALE PIPE THREAD BEYD DENOTES GROOVED CIVID DENOTES GROOVED CIVID DENOTES GROOVED PE DENOTES PLAIN BEND HUNIT WEIGHT DOES NOT INCLUDE ACCESSORIES (SEE ACCESSORY DRAWINGS) AMKALUP WATER PRESSURE 20 psi MIN (137 RP), 50 psi MAX (344 RP) 21 APPROVMATE DIMENSIONS DO NOT USE FOR PRE-FABRICATION OF CONNECTING PENS BEND BEND BEND BEND BEND BEND BEND BEND	ODEL # ATWB 10-3I18-Z SCALE NTS	EVAPCO, INC. Evapco WB3TM1806-DRC-SF	DATE 5/19/2024
(2) 4" [100] BFW FLUID IN	. (M)- FAN MOTOR LOCATION . HEAVIEST SECTION IS UPPER SECTION . MPT DENOTES MALE PIPE THREAD FPT DENOTES FEMALE PIPE THREAD BFW DENOTES BEVELED FOR WELDING GVD DENOTES GROOVED FLG DENOTES FLANGE PE DENOTES PLAIN END . +UNIT WEIGHT DOES NOT INCLUDE ACCESSORIES (SEE ACCESSORY DRAWINGS) . MAKE-UP WATER PRESSURE 20 psi MIN [137 kPa], 50 psi MAX [344 kPa] .*-APPROXIMATE DIMENSIONS DO NOT USE FOR PRE-FABRICATION OF CONNECTING PIPING . SERIES FLOW PIPING AND AUX. CROSSOVER DRAIN BY OTHERS 3/4" [19MM] DIA. MOUNTING HOLES. REFER TO RECOMMENDED STEEL SUPPORT DRAWING DIMENSIONS LISTED AS FOLLOWS: ENGLISH FT-IN	FACE B PLAN VIEW FACE A	FACE D
[643] 3 5/8" DRAIN 3" [80] MPT DRAIN 3" [80] MPT OVERFLOW 4 1/4" [108] 5'-11 3/4" 9'-9 3/4" [2991] FACE B	(2) 4" [100] BFW FLUID IN 1'-10 1/4" * [565] 2" [50] MPT MAKE-UP 2'-1 1/4" [643] 3 5/8" 3" [80] MPT DRAIN 5 1/4" [133]	2'-6 3/8" * - (2-6 3/8" * - (2-6 3/8" * - (2-4* [100] BFW FLUID OUT 13'-5 7/8" (4112) (5EE NOTE 7) (SEE NOTE 7) (SEE NOTE 7) (SEE NOTE 7) (SEE NOTE 7) (1580)	