UNIT CONDENSER			EV/A D	CO TR	IC ev	epeo °	DWG. # WV050906-DRC-ST	REV.
MODEL #	LRC 128	SCALE NTS	EVAP	CO, II	VC.	Ø	SERIAL #	DATE 5/13/2024
FPT DENOTES BFW DENOTE GVD DENOTE FLG DENOTES PE DENOTES 3. +UNIT WEIGH	S MALE PIPE THREAD S FEMALE PIPE THREAD S BEVELED FOR WELD S GROOVED S FLANGE	iNG				FACE C		
4. 3/4" [19mm] DI RECOMMEND 5. DIMENSIONS 6. * - APPROXIM, USE FOR PRE 7. MAKE-UP WA	A. MOUNTING HOLES. F ED STEEL SUPPORT DF LISTED AS FOLLOWS: E [ATE DIMENSIONS DO N -FABRICATION OF CON	REFER TO RAWING ENGLISH FT II [METRIC] [mm OT INECTING PIP	FACE B 5'-5	5/8"				FACE D
)	15'-2 1/4' [4629] FACE A		
	2'-6 3/8" * -						[6'-3"] ———————————————————————————————————	_
4" [100] PE - REFRIG IN 4" [100] PE - REFRIG OUT		1'-7	3'-7 1/2" 7 1/2"			CCESS DOOR		6'-7 3/4" [2026]
3 1/4" [83] TYP. →		M	3'-1/4" [919] 2 5/8"				-1" [25] MPT	1'-8 1/8" [511]
3" [80] MPT — OVERFLOW		Z	[67] [222] ł 7/8" 124]	-		3'-5 3/8" [2575]	MAKE-UP	ACCESS DOOR
2" [50] MPT — DRAIN	5'-5/8" [1540] FACE B	1'-8 7/8" [530]		1 5/8" 346]		15'-2 1/4' [4629] FACE A		
SHIPPING WEIGHT	5400 lbs+ [2450] kg	g+	OPERATING 8210 lbs+ [3	725] kg+	HEAVIEST SECTION WEIGHT	5400 lbs+ [2450] kg+	NO. OF SHIPPING SECTIONS	DRAWN BY: TLS